

Product Information

G 1781 High Precision Reference Thermometer with Micro-Probe Ø1.1 mm



- Highly precise calibration around 37°C e.g. for reference of medical products e.g. at IVF applications
- High resolution 0.01°C and precision
- Miniaturized precision probe Ø1.1 mm
- Calibratable / traceable
- robust, long battery life
- Made in Germany

Characteristics

The G 1781 is a high-precision reference thermometer for checking medical technology products like e.g. incubators, where the highest accuracy is required. The miniaturized probe is designed to be inserted in appropriate reference bores and to measure on site quickly and without distortion.

Precision, speed and reliability, packed in a compact and waterproof housing makes the device a reliable partner for professional users,

Technical Data

Measuring input: NTC 30K, high precision
Accuracy: at 37°C better ± 0.05 °C

Probe:
Diameter: Ø 1.1 mm
Probe length: 12 mm
Intermediate cable: 27 mm, Ø < 1 mm
Transition sleeve: Ø4 x 45 mm
Connection cable: 1.2 m PVC, permanently connected
Measuring range: 0.00 ... 80,00 °C
Resolution: 0.01 °C
Calibration: optional factory calibration (ISO),
test points: 0 °C, 37 °C, 70 °C

Standard functions: Min/Max/Hold
Auto power-off function

Additional functions:
Zero and slope correction

Ambient conditions -20 to 50 °C; 0 to 85 % r.h. (non-condensing)

Display 3 lines with battery status indicator,
Backlight, shatterproof screen,
overhead display at the push of a button

Operation 4 long-life buttons

Power supply 2*AA batteries (incl.)
Battery life >2500 h (without backlight,
with backlight >1000 h)
4 level battery status indicator
Automatic switch-off, adjustable

Housing Shatterproof ABS
Screwed battery compartment

Protection class IP40
Dimensions 108 * 54 * 28 mm (L*W*H)
Weight 125 g incl. battery

Product Information

Scope of supply

- Handheld without sensor (depending on set, please refer to „ordering code“)
- Test protocol, optional calibration certificate
- 2xAA batteries
- Manual

Ordercode


G1781 1. - 2.

1. Set-Option

- Device alone
- GKK1000 Device in case GKK 1000

2. Calibration

- without ISO-calibration certificate
- WPT3B ISO-calibration certificate WPT3B 0 / 37 / 70 °C



Probe dimensions in detail

Standard articles

- Instrument only, with temperature probe
G 1781 Art.-No.. 478418
- Device in case GKK 1000, ISO calibration WPT3 -0 °C, 37 °C, 70 °C
G1781-GKK1000-WPT3B Art.-No.. 473959

Accessories

Spare parts:

- Spare batteries 2x AA
GB-AA-2 Art.-No. 479249

Additional accessories:

- Protection bag with belt clip:
ST-G1000, Art.-No. 611373
- Metal belt clip self-adhesive:
GCLIP1000, Art.-No. 475820
- G 1000 table base and wall suspension:
G1000_BASE Art.-No. 481885
- Carrying case
GKK1000 Art.-No. 611603
- Rubber protection cover for G 1000 series
G1000-Cover Art.-No. 483958



PRC Technologies Corp., Ltd. ลาดพร้าว 101 กรุงเทพ 10240

โทรศัพท์ : 02 530 1714, 02 932 1711 มือถือ : 086 360 8600

อีเมล : contact@prctech.net LINE ID1 : prctec-info, LINE ID2 : @prctec